

Date: 6/12/2023

Date: 0/12/2025	
<u>Tender Name</u> : - Supply and deliver	ry of Medical Supplies Gadaref state . سم العطاء: توريد وتسليم معدات طبية في ولاية القضارف .
Project: Islamic Relief-	PR # 18358
Company Name:	اسم الشركة:
Address:	العنوان:
Contact Person:	ممثل الشركة:
Mobile Number:	رقم الموبايل:
Elect email:	البريد الالكتروني:

الإغاثة الإسلامية عبر العالم منظمة تطوعية تعمل في السودان منذ العام 1991 ، تسعي لتخفيف المعاناة عن الفقراء في العالم دون تمييز للجنس او العقيدة او الاصل ومنذ بداية عملها في السودان نفذت المنظمة بنجاح العديد من مشاريع التنمية والاغاثة في قطاعات المياه واصحاح البيئة ، الصحة ، التعليم ، سبل العيش ، الطوارئ ودعم الأيتام.

هذا العطاء لتوريد وتسليم معدات طبية في ولاية القضارف وفق الشروط المبينة أدناه.

- 1. الإلتزام بالكميات والأنواع المحددة بجدول المواصفات والكميات المرفق.
- 2. تقديم صور وكتيبات من معدات العطاء حسب المواصفات المطلوبة مرفقة مع كراسة العطاء ويتم مقارنتها مع المعدات المستلمة لمن يرسو عليه العطاء ، ترد لمن لم يرسو عليه العطاء.
 - 3. الكميات المطلوبة قد تزيد أو تنقص حسب الأسعار المقدمة والميزانية المتوفرة
 - 4. يتم ملء البيانات في كراسة العطاء فقط ، والأسعار يجب أن تكون شاملة كافة الرسوم

سيتم توقيع عقد توريد وتسليم معدات طبية في ولاية القضارف مع منظمة الإغاثة الإسلامية عبر العالم لمن يرسو عليه العطاء:

- أ. تقديم شهادة خلو طرف من الضرائب والزكاة
- ب. توريد كامل المواد خلال (20) يوما من تاريخ توقيع العقد.
- ج. يجب تقديم تفويض لتحصيل ضريبة القيم المضافه 17% من ديوان الضرائب وإلا لن يتم دفعه للمورد .
 - د. للمنظمة لجنة فنية لها الحق في رفض المواد غير المطابقة للمواصفات عند الإستلام.
 - فاتورة نهائية مختومة بختم الضرائب بعد تسليم المواد.
- 9. يتم سداد قيمة العطاء بالجنيه السوداني بشيك عقب إستلام كل الكميات بالمواقع المعنية و في التاريخ المحدد.
 - 10. يرفق المتقدم:
 - أ. شهادة تسجيل الشركة/إسم العمل
 - ب. شهادات الخبرة السابقة والرخصة التجارية
 - ج. ارفاق نسخة من تفويض بتحصيل القيمة المضافة من مصلحة الضرائب
 - د. اسكرين فورم (يستلم مع كراسة العطاء)
 - ه. صورة من إثبات الشخصية لمجلس إدارة/مدراء/أصحاب العمل
- 11. يتم تقديم العطاءات في ظرف مغلق مختوم بالشمع الاحمر يكتب عليه (عطاء توريد وتسليم معدات طبية في ولاية القضارف) ويودع بصندوق العطاءات بمكتب المنظمة ولاية القضارف حي الجمهوريه جنوب –او مكتب المنظمة بوادمدني- مارنجان- حلة حسن- جوار كلية الاندلس
 - Irw.Sudanprocurement@gmail.com .12
 - 13. الإلتزام بكل ما ورد من شروط أعلاه ، و لا ينظر في العطاءات غير المستوفية للشروط
 - 14. لا يمكن فتح صندوق العطاءات لسحب كراسة العطاء بعد الإيداع وعلي من يرغب في الإنسحاب وضع خطاب يفيد ذلك في صندوق العطاءات
 - 15. المنظمة غير مقيدة بقبول أقل أو أعلى عطاء
 - 16. للمنظمة الحق في تجزئة العطاء متى تراءى لها ذلك ، كما لها الحق في إلغاء كل أو بعض بنود العطاء.
 - 17. اخر موعد لتسليم العطاءات في يوم الخميس الموافق 2023/12/21 م الساعة الثالثة ظهرا.

قائمة الأجهزة والمعدات المطلوبة للمراكز الصحية

	Item	Technical Specifications	Qt	Unit	Total
		_	y	price	
1	Microscope	Body with 6V 20W Halogen for 220V, 50 Hz. Quadruple revolving nosepiece. Sturdy,base with supportive rubber feet. With low position, coaxial coarse and calibrated fine focus control, with graduation reading 2 microns per division. Total focusing 40 mm. Condenser adjustable. Built-in Power supply, halogen bulb adjustable. Double layer mechanical specimen stage. Dust cover, blue filter, immersion oil and instruction manual included. 2 pcs. 6V 20W halogen bulbs included. Binocular Head, 30° inclined, 360° rotatable, Interpupillary Distance 55 – 75 mm Objectives: ACHRO 4x/0.10 ACHRO 10x/0.2 ACHRO 40x/0.65, spring loaded ACHRO 100x/1.25, Oil, spring loaded	8		
2	White cell chamber	Treffice 100% 1120, on, spring fouced	10		
3	Electric Centrifuge digital 8 tube	Speed: not less than 600 rpm step of 100 Specimen capacity:8 tube/run Sample size: 10 ml tube Built in timer and speed control Digital display Brake Door lock and safety protected lid Power supply: 220VAC,50Hz	2		
4	Examination lamp	Lamp, Examination . Mobile on 5 Castors, 5 star-shaped Heavy and stable Stand. Halogen Type Height of LampHead shall be adjustable	8		

5	Couch& Examination Screen	Light Intensity shall be at least 15000 Lux with a Field radius of 17cm Minimum Color Intensity: 4300 °K. Single Reflector of 150mm Minimum Power rating: 1X40W Minimum. 220VAC/50Hz. Transformer, 24V DC shall be included Accessories /Spares: 5 Halogen Bulbs Standards Examination couch shall be made of a solid steel sheet and plate construction with anti-corrosive and antirust treated epoxy powder coating with upholstered top. Overall size of the table must not be less than 1890mm L x 600mm W x 825mm H. Swinging tray must be attached near headrest for BP apparatus and/or other health checkup minor equipment. The mattress shall be foldable and shall be designed to bend with the positioning of the bed when the backrest of the bed is adjusted. Three or four fold ward screen approx. total size 2450 w x 1650 h mm in three or four sections. Mild steel tubular construction with epoxy powder coated or better treated in three or four section 600mm span width at each side and 1210 mm span width in the middle) and mounted on wide spaced legs for each section, and each foot to have two swivel castors size 50mm	4	
6	Rack tube	Stander	10	
7	ESR tube	Stander	10	
8	ESR Rack	Stander	10	
9	Automatic Pipette	Stander	10	
10	Chemistry Analyzer Semi- Automatic	At least 100 tests/hr Including end point and kinetic measurement Capable of analysing serum, plasma, urine and CSF Automatic calibration Indication of abnormal values Computer interface	4	

		Analysis of Albumin, ALP, ALT, AST, BUN, Ca++, Cholesterol, CK, Cl-, CO2, Creatinine, Direct and total bilirubin, Glucose, Inorganic phosphorus, Iron, K+, LDH, Mg, Na+, Total protein, Triglycerides, Urea, Uric acid and others		
11	Electric suction	Front panel with transported handle 2 Jars, 2Lt. Each at least Mobile with 4 Casters Noise level: less than 50 dB Operating time: continuous operation Air flow rate of pump: around 35L/min Power: 220V/50Hz Filters and tubes are included Vacuum adjustment Vacuum gauge is included	4	
12	Dressing		8	
13	Trolley Dressing Tray		10	
14	Sterilization	Large size1, Medium 1 and small 1	8	
	Drums			
15	Hospital Medical Beds+ mattress	Standard hospital bed, 2 sections. Mounted on 4 swivel castors, heavy duty, 2 with brake. Transfer bars connect lower distal portions of the 2 foot-end and the 2 headend legs, providing maximal structural strength. Protective bumpers at all four corners. Bed-ends, finished with panels. Two section platform, epoxy-painted steel mesh with side supports to immobilize the mattress. Mattress cover removable via side zipper. Manually operated crank allows adjusting the backrest to 45-70 degree. Crank-handle folds away underneath the bed. High resistance to corrosion (tropical environment). Frame: epoxy coated tubular steel. Mattress: high density polyurethane foam, density is 28-30 kg/m3. Cover: plastic, flexible, highly tear resistant, anti-static, flame-retardant,	10	

		non-absorbing, waterproof and cleanable		
		with hospital-grade disinfection products.		
		Castor frame/bracket: steel or nylon.		
		Caster brake: total-lock type (wheel and		
		rotational lock).		
		Caster wheel: single wheel, mold-on type, non-hooded (for easy maintenance).		
		Wheel bearing: sealed bearing in the		
		swivel and the wheel.		
		Swivel is ball-bearing.		
		<u> </u>		
		Dimensions:		
		Sleeping surface: 200 x (80-90cm) (1 x		
		W).		
		Height of surface, without mattress, fixed: 50 cm.		
		Mattress: 11-12 cm (h).		
		Bed frame: (5-7) x 3 cm (h x w) 1.7-2mm		
		(thickness).		
		Leg frame: 3 cm x 2.0 mm (thickness).		
		Swivel castor wheels: 3 x 12.5 cm		
		(w*diameter).		
		Carrying capacity: min. 150 kg Knockdown construction		
		Knockdown construction		
16	Stethoscope	Chrome-plated. Dual-head chest piece	8	
	•	48 mm chest-piece has white diaphragm		
		Complete with 2 spare ear tips and a		
17	Th	spare diaphragm	20	
17	Thermometers		20	
10	Digital Section 2015	GOOD BRAND	0	
18	Sphygmomano	Wall type	8	
	meter	Mercury		
		Including cuff and tubes		
		Including basket		
19	Drip Stand		10	
20	Ventolins	Desk Type	8	
	Nebulizer	Nebulization: 0.4-0.7 ml/min		
		Max. Cup capacity: 8ml Particles:1-5 micron		
		Oscillating frequency: 2.4 MHz approx.		
		LCD display for time, and air flow		
	_	On/off button		

		In also dim a manufaction in a second of the			
		Including mouth piece, tubes, filters,			
		masks for infant and pediatrics			
		220v/50hz			
21	Adult scale +	Mechanical scale.	8		
	tall meter	Capacity:140kg x 100g.			
		High rod included.			
		Hand post included.			
		Wheels for transportation.			
		Platforms cover. + tall meter50250 cm			
22	Minor Surgery		8		
	Set				
23	Oxygen	Compact and easy to transport oxygen	8		
	Concentrator1	concentrator (Mobile on Castors)			
		The Oxygen Concentrator shall feature a			
	01	dual-head Compressor. One head			
		producing. Capacity: 1 to 5 l/Mn of O2			
		at 90% minimum at maximum flow			
		Pressure-compensated Flowmeter shall			
		permit use of long canula while			
		maintaining			
		accurate flow setting.			
		Safety Alarms: Audible and visual:			
		Power Failure, Restricted Flow, Low			
		O2			
		Pressure-relief Valve and thermal			
		protection of the Compressor			
		Double-insulated Unit, Two-prong plug			
		Flame-retardant Cabinet			
		Sound Level (ANSI): 50 dB average			
		Fixed humidifer Port and Recess shall			
		prevent bottle and connector breakage			
		Power Requirements: 220 VAC,50 Hz			
		Accessories:			
		O2 Tubing, 3 Face Masks (Adult,			
		Infant, New Born), Humidifier,			
		Set of Filters			
		Standards			
		CE;			
		EC			
24	Refrigerator	For medicine storage.	2		
- '		Upright Type] _		
		Internal volume not less than 250 lt. /			
		freezer - $40 \square 50$ lt.			
		Temperature controlled within the range			
		of $+2 \square \square + 8 \square \square \square$.			
		Number of shelves – 3 or 4.			
	I		ı	1	1

		With defrosting system			
		Power Requirements: 220 ± 10% V. 50			
		Hz			
25	Autoclave 50 L	Horizontal autoclave, benchtop Type for	4		
		CSSD, Laboratory, OutPatient/Wards			
		Sections			
		Self-contained ,front-loading and fully			
		automatic Unit with integrated Steam			
		Generator.			
		The Unit shall be single Manual Door			
		Type			
		Stainless Steel Chamber and Door:			
		Z3CN18/10			
		Capacity per cycle shall be at least 100L			
		for a Cycle time of not more than 25			
		ļ — — — — — — — — — — — — — — — — — — —			
		Mn.(Storilization Phase at 1249C)			
		Sterilization Phase at 134°C).			
		Sterilization shall be enhanced by the use			
		of Vacuum Cycle Digital temperature			
		control and timing, Pressure Control,			
		fully programmable cycle parameters			
		Low Water alarm, Door Safety Locks,			
		Program Cut-Out in case of Power			
		Failure,			
		Automatic Zeroing. Cycle End Alarm			
		During Cycle progress, Door is locked			
		into position by both Temperature and			
		Pressure Interlocks . Rapid single action			
		door closure shall be of concern			
		Electronically-operated Vent valve,			
		Automatic Air Purging, Over Pressure			
		Safety			
		Valve and Low Water Cut-Out with			
		Visual and Audible Alarm indication			
		shall be as			
		standard			
		The Unit shall be equiped with at least 4			
		Stainless Steel Trays			
		l •			
		Power Supply: 220VAC.50Hz.			
		Accessories:			
2.5	TO 11	4 Stainless Steel Trays		-	
26	Delivery table	Manufactured from reinforced epoxy-	8		
		painted steel tube			
		Three sections with independent manual			
		controls.			
		Trendelenburg position.			

	T	TD1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
		Third section extensible.		
		Top is upholstered with washable plastic	;	
		material flame retardant.		
		Complete with S.S. tray, and two		
		adjustable knee crutches, padded		
		shoulder rest handgrips, leg-holders,		
27	Pediatric scale	Capacity-0-15 kg	10	
		Graduation-10 gr.		
		Precision-+/- 10 gr.		
		Washable surface		
28	Delivery Set	Set contain: B.P.Handle No.3 - Qty.1 B.P.Handle No.4 - Qty.1 Dissecting Forceps Tooth 15cm - Qty.2 Dissecting Forceps Plain 15cm - Qty.1 Scissor Mayo St. 18cm - Qty.1 Scissor Mayo St. & Curved 16cm - Qty.1 Scissor Episectomy - Qty.1 Needle Holder 18cm - Qty.2 Placenta Puncture Forceps - Qty.1 Sponge Holder 20cm - Qty.2 Sponge Holder 26cm - Qty.1 Anterior Vaginal Retractor - Qty.1 Artery Forceps Curved 16cm - Qty.2 Cord Clips - Qty.1 Sim's Speculum Medium - Qty.1 Sim's Speculum Large - Qty.1 Towel Clip - Qty.4 S. S. Bowl 6 cm - Qty.2 Big Kidney Tray - Qty.1 Allis FORCEPS 8 " - Qty.2 Mosquito Artery cd - Qty.2	Each	
20	Oggi en Anhla		0	
29	Office table 120X70		8	
31	Office Chair		8	
31	Three		8	
	connected			
	chairs set			
	(patients			
	waiting area)			
			•	

32	Office		4				
	cupboard						
Sub	-total						
Tra	nsportation						
VA'	Т 17%						
Grand Total							
Manufacturer Please specify manufacturer and country of origin							
Model number Please specify model number							
Wa	Warranty						
Con	Comprehensive warranty for 2 year						

Amount in Words:	
Supplier Name:	
Address	
Supplier Signature:	